B.E. Sem VII CBSGS Mechanical Engg. CADICAMICAE

195/2016 11 am to 2 pm

QP Code: 31287

(CBSGS)(R-2012)

(3 hours)

[Total marks: 80]

N.B.: 1) Q. No. 1 is compulsory.

- 2) Attempt any three questions out of remaining five questions.
- 3) Assume suitable data if required.
- Q1 a) Explain wire frame modeling, surface modeling and solid modeling.

10

b) Write a manual part program for finishing a forged component as shown in Fig. 1. Assume the spindle speed and feed for machining as 500 rpm and 0.3 mm/rev respectively.




Fig. 1

- Q2 a) A Hermite cubic spline is defined by points (1, 1) and (6, 5), having tangent vectors as (0, 4) and (4, 0) respectively. Find the co-ordinates of parametric mid-point and slope at the same point.
 - b) Explain AS/RS and their types.

10

02 -) 1	Din J. Alandaria	Tours of the same	Acres de la companya de
co-crainates of a	triangle A (50, 20), E	3 1110 201 a	nd 10
		, (±±0, 20) a	110
stariabout i) V and	s and ii) Line y = x.		
Less about, IJ A-axi	s and iii Line $v = x$.		
	The state of the s		


l role of CIM elements.

10

- on matrix which aligns vector ${f K}$ along positive z-axis 10 + c ${f K}$,
- os involved in rapid prototyping, list the various rapid 10 ies and explain Stereo-lithography in detail.

- ع aj rmu me tran<mark>stormen C (80, 60), if it is re</mark>flec
 - b) Explain the nature and
- Q4 a) Find the transformati with vector V = aI + bJ
 - b) Explain the major step prototyping technolog

Q5 a) Write a complete APT part program to machine the outline of the geometry and drill a hole as shown in Fig. 2. The component is 5 mm thick. The end mill used is 10 mm in diameter and suitable drill. Assume suitable speed and feed for machining.



b) Find the general transformation matrix N for window to viewport mapping.

Q6 Write short notes on;

20

8

- a) Knowledge based Engineering
- b) Computer Aided Engineering
- c) CIM Hardware and Software
- d) Rapid Prototyping Applications