

H.T / Mech / CBGS / Nov - 16. / 19-12-16

Sem-V

Heat Transfer

Q. P. Code : 600902

[3 Hours]



[Total Marks:80]

- Notes:** 1) Question no.1 is **compulsory**.
2) Attempt any **THREE** from questionno.2 to 6.
3) Use illustrative diagrams wherever possible.
4) Use of Steam table is permitted.
5) Assume suitable data wherever required.

1. Solve any **Four** :- 20
- Draw a neat boiling curve for water and mark the different boiling regimes.
 - A steel ball 50mm in diameter and at 900°C is placed in still atmosphere of 30°C. Calculate the initial rate of cooling of the ball in °C/min. Take $\rho = 7800 \text{ kg/m}^3$, $C = 2 \text{ kJ/kg}^\circ\text{C}$ (for steel), $h = 30 \text{ W/m}^2^\circ\text{C}$. Neglect internal thermal resistance.
 - Explain non dimensional numbers used in convection heat transfer
 - Explain briefly the term thermal capacity and thermal diffusivity of material.
 - Define intensity of radiation. What is a solid angle? What is its unit?
2. a) A wall of a furnace is made up of inside layer of silica brick 120 mm thick covered with a layer of magnesite brick 240 mm thick. The temperature at inside surface of silica brick wall and outside surface of magnesite brick wall are 725°C and 110°C respectively. The contact thermal resistance between the two walls at the interface is 0.0035°C/W per unit wall area. If thermal conductivities of silica and magnesite bricks are 1.7 W/m°C and 5.8 W/m°C, calculate. 10
- The rate of heat loss per unit area of walls.
 - The temperature drop at interface.
- b) Derive the formula for rate of heat transfer for an insulated tip fin from the differential equation 10
- $$\frac{d^2 \theta}{dx^2} - m^2 \theta = 0$$
3. a) Air at 30°C flows with a velocity of 2.8 m/s over a plate 1000 mm (length) X 600 mm (width) X 25mm (thickness). The top surface of the plate is maintained at 90°C. If the thermal conductivity of the plate material is 25 W/m°C, calculate: i) heat lost by the plate; ii) bottom temperature of the plate for the steady state condition. The thermo - physical properties of air at mean film temperature at 60°C are $\rho = 1.06 \text{ kg/m}^3$, $k = 0.02894 \text{ W/m}^\circ\text{C}$, $C_p = 1.005 \text{ kJ/kg}^\circ\text{C}$, $Pr = 0.696$; $\nu = 18.97 \times 10^{-6} \text{ m}^2/\text{s}$. Choose the appropriate relation from the following: 10
- $\overline{Nu} = 0.664 (Re_L)^{1/2} (Pr)^{1/3}$ - For Laminar flow;
 $\overline{Nu} = 0.036 (Re_L)^{0.8} (Pr)^{1/3}$ - For Turbulent flow
- b) With the help of dimensional analysis method prove that for free convection 10
- $$Nu = \text{constant} \times (Gr.)^m \times (Pr.)^n$$

[TURN OVER

4. a) State and explain the reciprocity theorem. Derive the equation $A_1 F_{1-2} = A_2 F_{2-1}$. 10
 b) An electric wire of 0.25mm diameter, $\epsilon=0.4$ is placed within a tube of 2.5 mm diameter, $\epsilon=0.6$ having negligible thickness. This tube in turn is placed concentrically within a tube of 5 mm diameter, $\epsilon=0.7$. Annular spaces can be assumed to be evacuated completely. If the surface temperature of the outer tube is maintained at 5°C , what must be the temperature of wire so as to maintained the temperature of inner tube at 120°C ? 10
5. a) Derive the expression for log mean temperature difference in a counter flow heat exchanger. State your assumption. 08
 b) In a certain double pipe heat exchanger hot water flows at the rate of 50000 kg/hr and gets cooled from 95°C to 65°C . At the same time 50000 kg/hr of cooling water at 30°C enters the heat exchanger. The flow conditions are such that overall heat transfer coefficient remains constant at $2270\text{W/m}^2\text{K}$. Determine the heat transfer area required and the effectiveness, assuming two streams are in parallel flow. Assuming for the both streams $C_p = 4.2\text{ kJ/kg K}$. 08
 c) Explain Heat Exchangers effectiveness. 04
6. a) Write short note on **any Two** of the following - 08
 i) Heisler Chart.
 ii) Explain efficiency and effectiveness of fin.
 iii) Time constant of thermocouple.
 b) Explain Hydrodynamic and thermal boundary layer. 04
 c) A steel rod ($K= 32\text{ W/m}^\circ\text{C}$), 12 mm in diameter and 60 mm long, with an insulated ends to be used as spine. It is exposed to surroundings with a temperature of 60°C and a heat transfer coefficient of $55\text{ W/m}^2\text{C}$. The temperature at the base of the fin is 95°C . Determine- 08
 (i) The fin efficiency
 (ii) The temperature at the edge of the spine;
 (iii) The heat dissipation.
-